

1080P real-time multi-touch portable 4 channel standalone NVR

AiP-Q4U

1080P real-time multi-touch portable 4 channel standalone NVR

- Portable NVR
- Multi-touch screen supported
- 1080P 4 channel real-time NVR up to 24 Mbps throughput
- Full HD 1920×1080 HDMI output
- Support one 2.5" SATA X1 or SSD HDD X1
- External USB DVD/RW.
- AiM software HD 2.6 supported.
- 3G mobile phone (iPhone, iPad, Android, and Blackberry) solutions provided.



AiP-Q4U

		NVR	
Model		Q4U	
		Internal 2.5" SATA or SSD HDD	
IP video supports		Network camera, network speed dome, and video server	
IP video Input		Up to 4-channels 1080P	
Max network throughput		24 Mbps	
HDD disk supported		SATA port x 1	
Recording	Recording mode	External alarm / motion detection / schedule / manual	
	Resolution	1080P/ 720P/ D1/ VGA	
	Recording video	1080P/ 720P/ D1/ VGA	
	Schedule	7 day * 24 hrs time table, recording mode configurable	
Backup	Backup	USB 2.0 flash disk / HTTP file download / audio supported	
	DVD/RW	External USB DVD/RW	
Playback	Resolution	1080P/ 720P/ D1/ VGA	
	Playback video	1080P/ 720P/ D1/ VGA	
	Speed	FR: 2X, 4X, 8X,16X, 32X, 64X FF: 2X, 4X, 8X,16X, 32X, 64X	
Video output	HDMI output	1920 x1080P	
	Backlight saving	LCD backlight saving mode	
	Multi-touch	Support USB multi-touch screen	
Multiplexer	Multiplexer	Freeze	
	Split screen	4	
	Digital zoom	Up to 64X on live and playback	
Management	Reports	Full alarm, configuration, and operation reports exporting over HTTP or US	SB
	Authentication	User authentication with feature configurable	
	Recording day	Recording day calculator	
Alarm/event	Alarm/event	DI * 2 and DO* 2 (NO/NC)	
	Motion	Motion grid 20*12 each channel, 8 sensitivities	
	Event	External alarm, video loss, stop recording, power recovery, motion detection schedule, logon, HDD format	on,
	Email	Alarm notification with JPEG attachments	



	NVR				
Model		Q4U			
Accessories	Accessories	Remote controller addressable up to 255 NVRs			
	P/T/Z protocol	pelco D/ P			
	Keyboard	Yes			
	IR receiver	Yes			
	RS-485/RS-232	RS-485 keyboard connector Input * 1 , 12V output			
	Mouse	USB, mouse-click, mouse scroll, mouse drag			
	Audio out	RCA, 1 output			
	Remote control	Yes			
	Network ports	Gigabit LAN, RJ45 *1			
	Network	Direct Internet browser access / multiple users access			
	Protocols	ARP / TCP/IP / UDP / HTTP / SMTP / FTP / DDNS			
Network ports	Web	Live / event log & time search playback / AVI			
	NVR status	HTML NVR status			
	IPScan	IP scan supported, automatically quick IP address setup for IP cameras and NVRs			
Software	Backup manager	Multiple NVRs FTP file download and multi-channel playback			
	Mobile phone	iPhone, iPad, Android and Blackberry mobile phone supported			
Others	WDT	Hardware watchdog timer			
	DST	Daylight saving time			
	Multilanguage	English, Chinese, Spanish, German, French, Portuguese, Italian, Turkish			
	CPU/OS	ARM cortex A9 processor @ 600 MHz, linux 2.6 kernel			
Power	Power	DC 12V, 4.2A / 48W			
	Working env.	Temp: 0°C ~ +45°C / Humidity: 0%~80%			
	Dimension	183 * 130 * 43 mm			
	Weight	0.5 Kg (w/o HDD)			